INCATI

Innovative Carpet Tiles

CORAL - CORAL LINES

version 27/09/2019
replaces 13/09/2019

Manufacturing type	Herstellungsart	Mode fabrication	Productie methode			**tufted 1/10"**	
Construction	Struktur	Structure	Structuur			**loop pile**	
Pile composition	Polmaterial	Couche d'usure	Poolsamenstelling			**100% PA 6 BCF**	
Dye method	Farbgestaltung	Coloration	Kleurverwerking			**solution dyed**	
Primary backing	Trägermaterial	Premier dossier	Tuftdoek			**polyester fleece**	
Secondary backing	Rückenausrüstung	Dossier	Rug			**bitumen**	
Pile weight	Poleinsatzgewicht	Poids de velour	Poolgewicht	ISO 2424	g/m2	**485**	(+/-)
Total weight	Gesamtgewicht	Poids total	Totaal gewicht	ISO 8543	g/m2	**4.200**	(+/-)
Pile height	Polhöhe	Hauteur du velours	Poolhoogte	ISO 1766	mm	**3,0**	(+/-)
Total height	Gesamtdicke	Epaisseur totale	Totale dikte	ISO 1765	mm	**5,5**	(+/-)
Tuft density	Noppenzahl	Nombre de touffes	Aantal punten	ISO 1763	/m2	**175.000**	(+/-)
Size	Abmessung	Dimension	Afmeting		cm	**50 x 50**	
Packing	Verpackung	Emballage	Verpakking			**20 per box**	**5 m2**
Classification	Klassifikation	Classement	Gebruiksklasse	EN 1307		**33**	heavy commercial
Comfort rating	Komfortklasse	Classement confort	Comfort klasse	EN 1307		**LC 1**	
Castor chair	Stuhlrolleneignung	Chaise à roulettes	Rolstoelgeschikt	EN 985		**A**	intensive
Dimensional stability	Dimensionstabilität	Stabilité dimensionnelle	Dimensionele stabiliteit	EN 986		**≤ 0,2%**	
Fire resistance	Brennverhalten	Comportement feu	Brandgedrag	EN 13501-1		**Bfl-S1**	loose laid
Permanent antistatic	Permanent Antistatisch	Antistatique permanent	Permanent antistatisch	ISO 6356	kV	**≤ 2,0**	
Transversal resistance	Durchgangswiderstand	Résistance transversale	Doorgangsweerstand	ISO 10965	Ω	**≥ 10^{10}**	
Thermal resistance	Wärmedurchlaßwiderstand	Résistance thermique	Warmtedoorlaatweerstand	ISO 8302	m2/K/W	**0,066**	
Sound absorption	Schallabsorptionsgrad	Absorption phonique	Geluidsabsorptie	ISO 354	α_w	**0,15**	
Impact sound reduction	Trittschallverbesserungmaß	Isolation phonique	Geluidsisolatie	ISO 10140	ΔL_w	**23 dB**	
				ISO 10140	ΔL	**35 dB**	(1000 Hz)
Colour fastness light	Lichtechtheit	Solidité à la lumière	Lichtechtheid	ISO 105 B02		**≥ 8**	
Rubbing fastness	Reibechtheit	Solidité au frottement	Wrijfechtheid	ISO 105 X12		**≥ 4-5**	
				DIBt Nr.		**Z-156.601-1467**	

SDN solution dyed nylon bleach cleanable yarn

19
EN 14041
DOP 000583T-001

TAPIBEL NV
Industrielaan 4
B-3900 Pelt
Belgium
+32 11 80 48 50
sales@incati.be
www.incati.be

EN 1307
for use as floorcovering in buildings (EN 14041)
accordings to the manufacturer's specification

TÜV PROFI CERT product 70 710 5632-2 www.proficert.com
tested for emissions, harmful substances

TÜV Emission testing
Results comply with emission threshold of
- AgBB - Germany
- Belgian VOC regulation
- BREEAM Exemplary level
- French VOC regulation
- LEED V4 (outside North America)

ÉMISSIONS DANS L'AIR INTÉRIEUR* A A+ A B C

INSTALLATION

ALSO AVAILABLE



MAINTENANCE

visit our website www.incati.be/en/faq-carpet-tiles
for more detailed information

These technical details are approximate. Complete specification details and associated certificates together with tolerances applying to the above can be provided upon request, if available. We reserve the right to alter specifications without notice. Due to the method of manufacture, perfect pattern/colour matching cannot be guaranteed.
Shading/pile reversal might occur in cut pile carpets, without affecting overall quality and suitability. It is not considered as a manufacturing fault.